


HOISTING AND LIFTING APPLICATION/NON ROTATING ROPES

Technical characteristics:

- 24 strands at 7 wires compacted
- Strength 1960N/mm² or 2160N/mm²
- Surface : Galvanized or Ungalvanized
- Tolerance diameter: 0 / + 4%
- High rotation resistance
- Compacted to extend cycle of life and reduce abrasion of pulleys
- Ordinary or Lang lay
- According to Norms EN 12385-4


Main Application:

- Main host rope used on Tower Cranes, Mobile Cranes, Dockside Cranes, Crawler cranes.



Non rotating 24xK7 2160N/mm²

Ø	kg/mt	MBL
8	0,31	63
9	0,39	80
10	0,48	96
11	0,58	119
12	0,69	139
13	0,81	160
14	0,94	185
15	1,06	216
16	1,25	245
17	1,35	273
18	1,57	308
19	1,74	342
20	1,91	381
21	2,14	422
22	2,32	460
23	2,51	506
24	2,76	552
26	3,25	647
28	3,78	751
30	4,34	862




Non rotating 24xK7 1960N/mm²

Ø	kg/mt	MBL
8	0,31	59
9	0,39	75
10	0,48	91
11	0,58	112
12	0,69	131
13	0,81	150
14	0,94	174
15	1,06	200
16	1,25	228
17	1,35	258
18	1,57	288
19	1,74	322
20	1,91	356
21	2,14	393
22	2,32	430
23	2,51	471
24	2,76	512
26	3,25	598
28	3,78	696
30	4,34	798




HOISTING AND LIFTING APPLICATION/NON ROTATING ROPES



Non rotating 24x7 2160N/mm²

Ø	kg/mt	MBL
8	0,28	57
9	0,35	73
10	0,44	87
11	0,53	108
12	0,63	126
13	0,74	146
14	0,86	168
15	0,96	197
16	1,14	223
17	1,23	248
18	1,43	280
19	1,58	311
20	1,74	347
21	1,95	384
22	2,11	419
23	2,28	460
24	2,51	502
26	2,96	589
28	3,44	683
30	3,95	784



Non rotating 24x7 1960N/mm²

Ø	kg/mt	MBL
8	0,28	54
9	0,35	68
10	0,44	83
11	0,53	102
12	0,63	119
13	0,74	137
14	0,86	159
15	0,96	182
16	1,14	207
17	1,23	235
18	1,43	262
19	1,58	293
20	1,74	324
21	1,95	357
22	2,11	391
23	2,28	429
24	2,51	466
26	2,96	544
28	3,44	633
30	3,95	726

ADMINISTRATION AND PRODUCTION : Contrada Cabiano 39,
3065 RIPATRANSONE (AP) TEL. +39 0735 90227 / +39 0735 90278
VAT NUMBER: 02305440444 - EMAIL della.cianci@mpwireropes.com
website: www.metalpress-wireropes.com

METAL PRESS

