


HOISTING AND LIFTING APPLICATION/ ROPES FOR HOISTING EQUIPMENT IN GENERAL/8 STRANDS

Technical characteristics:

- 8 strands at 26 wires WS compacted
- Strength 1960N/mm² or 2160N/mm²
- Surface : Galvanized or Ungalvanized
- Tolerance diameter: 0 / + 5 %
- Rope very firm and suitable for impact load.
- Compacted to have higher breaking load and wear hardness and extend service of life.
- Ordinary lay


Main Application:

- Main host rope for steelworks ladle cranes and container cranes
- Main hoist line. Boom hoist line for grabbing cranes, grab closing mine and racking rope for unload cranes.
- Suitable for working in hard conditions where high breaking load and abrasion resistance is required.



8XK26WS+IWRC R.1960N/mm²

Ø	kg/mt	MBL
8	0,341	59
9	0,429	75
10	0,528	92
11	0,528	111
12	0,759	133
13	0,891	156
14	1,034	181
15	1,188	207
16	1,353	236
17	1,496	266
18	1,672	298
19	1,87	333
20	2,068	368
21	2,277	406
22	2,497	446
23	2,739	487
24	2,981	531



8XK26WS+IWRC R.2160N/mm²

Ø	kg/mt	MBL
8	0,341	65
9	0,429	82
10	0,528	102
11	0,528	123
12	0,759	146
13	0,891	172
14	1,034	199
15	1,188	228
16	1,353	260
17	1,496	293
18	1,672	329
19	1,87	366
20	2,068	406
21	2,277	448
22	2,497	491
23	2,739	537
24	2,981	585

